

1325B Bentonite & Lubrication Pump



Part No. FA08269F

- **Designed For GBM Bentonite & Lubrication Applications •**
- **Pumping Fluid Mixtures Up To 50 Marsh Funnel Seconds •**
- **Compact Footprint For Job Site Positioning •**



FEATURES

- Pumping capabilities of water, water with polymer and bentonite up to 50 seconds (Marsh Funnel).
- Bulkhead connections for pressure and return lines.
- Aggressive in-tank agitator keeps mixture blended in tank.
- Open/close valve at tank outlet.
- In-line suction strainer to supply pump.
- Sized for container storage during cold weather operation.

SPECIFICATIONS

Dimensions:

Height 58 in. (1,473 mm)
Width 46.5 in. (1,181 mm)
Length 88.25 in. (2,242 mm)
Weight (empty tanks) 1,000 lbs. (454 kg)
Weight (full tanks) ... 3,700 lbs. (1,678 kg)

Power Unit:

Gasoline Engine @ 3,600 rpm .. 14 HP (10.4 kW)

Drive System Direct Drive

Agitator Hydraulic-Driven, In-Tank

Pump

Pump Flow 6 gpm (22.7 L/min)

Max. Pressure Rating 2,500 psi (17,237 kPa)

Fluid Capacities

Fuel Tank 1.9 gal. (7.3 L)

Jetting Tank 325 gal. (1,230 L)

Engine Oil 1.16 qt. (1 L)

Hydraulic Reservoir 15 gal. (57 L)