

Upsize Tooling - Auger Boring Adapter 36/530



Part No. FA48180F

- **Designed For Use With GBM 4800 Series Thrust Frame** •
- **36" OD With Maximum 100,000 Ft-Lb Torque** •
- **Maximum 530,000 Lb Jacking Force** •



FEATURES

- Auger boring adapter assembly with integral thrust bearing and planetary gear box.
- Eliminates the requirement of an auger boring rig on job site.
- Wear strips on frame to reduce friction and wear on rail.
- Bi-fold door restricts access to dirt paddles.
- Quick mounts allow for swift changeover from pilot tubes.
- Lift eyes provide easy handling of assembly.

SPECIFICATIONS

Dimensions

Height	37.13 in. (943 mm)
Width	62.3 in. (1,582 mm)
Length	57.84 in. (1,469 mm)
Weight	approx. 4,800 lbs. (2,177 kg)

Dirt Paddle	2 Scoop
Drive Shaft	5 in. (127 mm) hex

Drive System

Thrust Bearing Gear Ratio	4.17:1
Output Torque (Max)...	43,800 ft-lb/108,400 ft-lb
Speed/Output Torque ...	8.5 rpm @ 100,000 ft-lb, ... 11 rpm @ 75,000 ft-lb, 19 rpm @ 41,000 ft-lb

Diameter	36 in. (914 mm) OD
Dirt Chute	Bi-Fold Door

